



GSG100

Gas Shrink System

Complete with Hose and Regulator

The new Pacplus GSG100 gives you stronger build quality and more power, but is also ergonomically designed for safe and comfortable use. The nozzle is protected by an integral heat shield and the burner cooling is aided by the propane gas flow.

Shrink wrapping large consignments with the Pacplus GSG100 Gas Shrink System

- > improves load stability
- > enhances protection against weather and dust contamination
- > enables outside storage
- > allows easy identification of securely wrapped contents
- > acts as a deterrent to pilferage

Technical Data	Fuel	Propane gas
	Fuel Container	Standard industrial propane cylinder
	Ignition	Piezo crystal
	Gas Pressure	3.5 bar (50 psi)
	Heat Variable	32kw (110,000 BTU)
	Gas Consumption	2kg/hr (5lb/hr)
	Weight	approx. 1kg
	Hose Lengths	8mtr
	Burner Safety	Auto cut-off on trigger release
	Regulator	Excess failure valve
Maintenance	Occasional drop of oil as supplied	

Pacplus heat shrink accessories and consumables include:



PFD/1
Shrink Film
Roll Dispenser



PCT
Gas Shrink
Trolley
*Gas cylinder
not included



A wide range of polythene shrink film in centre fold, gusset tubing and bag on roll configurations

